



ENEOS GRAND-LA 10W-40

New Generation low SAPS technology Heavy Duty Diesel Engine Oil

ENEOS GRAND-LA 10W-40 is the new generation Heavy Duty Diesel Engine Oil based on Low SAPS technology (Low Sulphur, Sulphated Ash and Phosphorus) to protect the exhaust gas after-treatment systems of heavy duty vehicles, trucks, busses and construction machinery. Specially formulated for the lubrication of the latest generation of engines (EURO 4 and EURO 5) equipped with Diesel Particulate Filters and EURO 4 engines equipped with selective catalytic reduction (SCR) units. Provides ultimate performance and protection also for EURO 3 and older engines from Europe, USA and Japan

APPLICATIONS

- **Ultimate Engine Oil Performance**

This oil offers outstanding performance in high-speed heavy duty European diesel engines and is particularly designed or suited for Daimler, VOLVO Trucks and MAN Euro IV & V engines fitted with diesel particulate traps (& exhaust after-treatment devices) under all operating conditions.

- **CNG Engine oil performance**

Suitable for use in buses and trucks fitted with engines designed to run on 100% CNG but requiring relatively high TBN oils in order to adequately control deposits and wear (i.e. MB, MAN and Volvo engines).

- **Recommended for European, American and Japanese engines**

Universal Oil for use in Cummins, Mack, Caterpillar and most Japanese engines.

FEATURES & BENEFITS

- **Exceptional piston cleanliness**

A unique oil formulation to offer exceptional piston cleanliness, resulting in the cleaner, efficient and reliable engine.

- **Extended engine life**

This oil exceeds the demanding wear protection standards of a wide range of European, American and Japanese engines providing effective protection under all operating conditions. This oil is effective at minimising bore polish and valve-train wear, thus maximising engine life and minimising costly downtime and maintenance.

- **Shear stable**

The extremely stable viscosity index improver used in this oil is highly resistant to viscosity shear. When subjected to heavy mechanical shearing action, this feature controls the viscosity of the oil throughout its service life, reducing oil consumption and minimising wear.

- **Fuel economy**

This oil offers considerable savings in fuel consumption, (compared to conventional SAE 15W40), without compromising on engine protection or increasing oil consumption.

- **Lower operating costs**

This oil makes a significant contribution towards reducing operating cost of vehicle through:

- Reduced downtime
- Sustained high performance for life of the vehicle
- Maximising particulate trap filter life
- Fuel economy
- Maximising vehicle resale through demonstrated excellence in maintenance

SPECIFICATIONS & APPROVALS

- API CI-4
- ACEA E6/E7/E9-16
- Mercedes Benz: 228.51
- MAN: M3477, M3271-1
- MTU Type 3.1
- Volvo VDS-3
- Renault Trucks RXD, RLD-2, RGD



- MAC EO-N*
- Cummins CES 20076/77
- DAF Truck – Meet Requirements
- Deutz DQC III-10 LA, DQC TTCD

PACK SIZES

20 Litres Pail, 208 Litres Drum, 1000 Litres IBC

TYPICAL PROPERTIES

SAE viscosity grade	10W-40
Density (20°C), g/cm ³	0.864
Flash point (COC), °C	238
Kinematic viscosity	
(40°C), mm ² /s	101.4
(100°C), mm ² /s	14.8
Viscosity at HTHS, mPas (cP)	4.2
Viscosity index	152
Pour point, °C	-39.0
TAN, mgKOH/100g	2.3
TBN, mgKOH/100g	8.1
Sulphated Ash, % w/w	1.5

Note: The typical properties may be changed without notice. (April 2024)

THE RECOMMENDATIONS OR SUGGESTIONS MADE IN THIS SHEET ARE MADE WITHOUT GUARANTEE OR REPRESENTATION AS TO RESULTS. THE CONTENT OF THIS SHEET IS CORRECT TO THE BEST OF OUR KNOWLEDGE. WE ADVISE THE READER TO CAREFULLY EVALUATE THE PRODUCT CHOICE FOR CRITICAL APPLICATIONS TOGETHER WITH THE SUPPLIER. WE DO NOT ACCEPT RESPONSIBILITY FOR DAMAGE AS A CONSEQUENCE OF INCOMPLETENESS OR, NEGLIGENCE AND INACCURACIES IN THIS INFORMATION SHEET. ALL TERMS OF SALE OF THE SUPPLIER CAN BE APPLIED HERE.