



## ENEOS ULTRA-M 0W-20

**Fully synthetic oil for Mercedes-Benz, delivering superior fuel efficiency, low emissions, and optimal cold-start performance.**

**ENEOS ULTRA-M 0W-20**, is a cutting-edge, fully synthetic engine oil engineered specifically for the latest Mercedes-Benz engines. This ultra-low viscosity 0W-20 formulation utilizes advanced low-friction additive technology to deliver exceptional fuel economy and reduced emissions, meeting stringent environmental standards. With its high viscosity index and low-friction design, the ULTRA-M 0W-20 ensures optimal cold-start performance, minimizes engine wear, and provides superior lubrication to keep pace with the evolving demands of modern Mercedes-Benz powertrains.

### SPECIAL FEATURES

#### 1. Cutting-Edge Synthetic Performance

Harnessing the power of premium synthetic base oils, the ENEOS ULTRA-M 0W-20 offers superior lubrication and protection for your Mercedes-Benz engine. Its high viscosity index ensures optimal oil flow at all temperatures, delivering outstanding cold-start performance for maximum protection from the moment you start your engine.

#### 2. Ultra-Low Viscosity Fuel Saver

Boasting an SAE 0W-20 ultra-low viscosity grade, the ENEOS ULTRA-M 0W-20 is a true fuel economy champion. Its advanced low-friction additive technology minimizes internal engine friction, resulting in exceptional fuel efficiency and reduced emissions. This innovative formulation helps meet strict environmental regulations while delivering tangible savings at the pump.

#### 3. Engineered for Modern Power

ENEOS ULTRA-M 0W-20 is engineered to keep pace with the evolving demands of Mercedes' cutting-edge powertrains. Its advanced formulation minimizes engine wear and tear, extending engine life and ensuring optimal performance in Mercedes' latest high-efficiency engines. This oil is the perfect companion for your modern Mercedes, delivering uncompromising power and reliability.

### PERFORMANCE LEVELS

- ACEA C5
- Mercedes-Benz MB 229.71

### APPLICABLE VEHICLES

Recommended for Mercedes-Benz vehicles requiring 0W-20 viscosity, MB 229.71 approval.

### PACK SIZES

1L, 4L, 20L, 60L, 208L

### TYPICAL PROPERTIES

SAE viscosity grade	0W-20
Density (15°C), g/cm <sup>3</sup>	0.8431
Flash point (COC), °C	234
Kinematic viscosity (40°C), mm <sup>2</sup> /s	42.78
(100°C), mm <sup>2</sup> /s	8.29
Viscosity index	173
Pour point, °C	-45.0
TAN mgKOH/g	1.77
TBN mgKOH/g (HClO4)	7.94

Note: The typical properties may be changed without notice.

(April 2024)

THE RECOMMENDATIONS OR SUGGESTIONS MADE IN THIS SHEET ARE MADE WITHOUT GUARANTEE OR REPRESENTATION AS TO RESULTS. THE CONTENT OF THIS SHEET IS CORRECT TO THE BEST OF OUR KNOWLEDGE. WE ADVISE THE READER TO CAREFULLY EVALUATE THE PRODUCT CHOICE FOR CRITICAL APPLICATIONS TOGETHER WITH THE SUPPLIER. WE DO NOT ACCEPT RESPONSIBILITY FOR DAMAGE AS A CONSEQUENCE OF INCOMPLETENESS OR NEGLIGENCE AND INACCURACIES IN THIS INFORMATION SHEET. ALL TERMS OF SALE OF THE SUPPLIER CAN BE APPLIED HERE.