



SAFETY DATA SHEET

ENEOS PREMIUM HYPER FA 5W30

According to regulation (EU) No. 2015/830

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name ENEOS PREMIUM HYPER FA 5W30

Internal identification A3/B4-12

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Engine oil.

1.3. Details of the supplier of the safety data sheet

Supplier JX Nippon Oil & Energy Europe Limited
Bury House, 2nd Floor
31 Bury Street
London, EC3A 5AR, UK
+44 20 7186 0402
+44 20 7186 0419
Gurjeet.Singh@noeu.jx-group.eu

Contact person Gurjeet Singh -Gurjeet.Singh@noeu.jx-group.eu

1.4. Emergency telephone number

Emergency telephone Emergency:112
Poison Centres

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Aquatic Chronic 3 - H412

Classification (67/548/EEC or -
1999/45/EC)

2.2. Label elements

Hazard statements H412 Harmful to aquatic life with long lasting effects.

Precautionary statements P273 Avoid release to the environment.
P501 Dispose of contents/container in accordance with national regulations.

2.3. Other hazards

No data available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

ENEOS PREMIUM HYPER FA 5W30

LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASE (Note L)		60-80%
CAS number: 72623-87-1 EC number: 276-738-4		
Classification Not Classified		
Styrene hydrocarbon polymer		1-5%
CAS number: —		
Classification Aquatic Chronic 4 - H413		
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts		<1%
CAS number: 68649-42-3 EC number: 272-028-3		
Classification Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Aquatic Chronic 2 - H411		
Phenol, dodecyl-, branched		<1%
CAS number: 121158-58-5 EC number: 310-154-3		
M factor (Acute) = 1 M factor (Chronic) = 10		
Classification Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Repr. 2 - H361f Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410		
DIPHENYLAMINE		<1%
CAS number: 122-39-4 EC number: 204-539-4		
M factor (Acute) = 1 M factor (Chronic) = 1		
Classification Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT RE 2 - H373 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

ENEOS PREMIUM HYPER FA 5W30

Inhalation	Move affected person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.
Ingestion	Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Get medical attention if any discomfort continues.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	No specific symptoms known.
Ingestion	No specific symptoms known.
Skin contact	No specific symptoms known.
Eye contact	No specific symptoms known.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations.
-----------------------------	------------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m ³ .
-------------------------	--

5.3. Advice for firefighters

Protective actions during firefighting	Avoid breathing fire gases or vapours. Fight fire from safe distance or protected location. Control run-off water by containing and keeping it out of sewers and watercourses.
Special protective equipment for firefighters	Use protective equipment appropriate for surrounding materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	For personal protection, see Section 8. In case of spills, beware of slippery floors and surfaces.
-----------------------------	--

6.2. Environmental precautions

Environmental precautions	Do not discharge into drains or watercourses or onto the ground. Avoid or minimise the creation of any environmental contamination. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.
----------------------------------	---

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses. For waste disposal, see Section 13.
--------------------------------	---

6.4. Reference to other sections

ENEOS PREMIUM HYPER FA 5W30

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

No data available.

DIPHENYLAMINE

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³

Short-term exposure limit (15-minute): WEL 20 mg/m³

WEL = Workplace Exposure Limit

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients. Provide adequate ventilation.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.

Other skin and body protection

Wear suitable protective clothing as protection against splashing or contamination.

Hygiene measures

Wash promptly if skin becomes contaminated. Promptly remove non-impervious clothing that becomes contaminated. Contaminated clothing should be placed in a closed container for disposal or decontamination. When using do not eat, drink or smoke.

Respiratory protection

No specific recommendations. Respiratory protection may be required if excessive airborne contamination occurs.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Flash point	Min.220 °C
Bulk density	0,84-0,86 g/cm ³ @15°C (ASTM D 4052)

ENEOS PREMIUM HYPER FA 5W30

Viscosity 10,00-13,00 mm²/s @ 100°C

9.2. Other information

Other information None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Will not polymerise.

10.4. Conditions to avoid

Conditions to avoid Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition products Fire creates: Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Germ cell mutagenicity

Genotoxicity - in vitro No information available.

Genotoxicity - in vivo No information available.

Carcinogenicity

Carcinogenicity No information available.

Reproductive toxicity

Reproductive toxicity - fertility No information available.

Reproductive toxicity - development No information available

Specific target organ toxicity - single exposure

STOT - single exposure No information available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No information available.

Inhalation No specific health hazards known.

Ingestion May cause discomfort if swallowed.

Skin contact Liquid may irritate skin.

ENEOS PREMIUM HYPER FA 5W30

Eye contact May cause temporary eye irritation.

SECTION 12: Ecological Information

Ecotoxicity Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

Toxicity No data available.

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects No information required.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information The packaging must be empty (drop-free when inverted).

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Environmental Manager must be informed of all major spillages. Avoid the spillage or runoff entering drains, sewers or watercourses.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

ENEOS PREMIUM HYPER FA 5W30

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

Guidance Workplace Exposure Limits EH40.
CHIP for everyone HSG228.
Safety Data Sheets for Substances and Preparations.
Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Key literature references and sources for data This SDS is prepared based on the information received from the product raw material.

Revision comments This is first issue.

Issued by ONUR CANSEVER/ Tecnology Center Laboratory Manager - TSE Certificate Number : GBF-1467 Hazal KUBİLAY / Teknology Center Laboratory Asistant Specialist -TSE Certificate Number : GBF-2166

Revision date 02/08/2016

Revision 0.0

Supersedes date 02/08/2016

SDS number 20649

Hazard statements in full H301 Toxic if swallowed.
H311 Toxic in contact with skin.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H361f Suspected of damaging fertility.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
H413 May cause long lasting harmful effects to aquatic life.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.